

11/23/99



jc713 U.S. PTO

UTILITY PATENT APPLICATION TRANSMITTAL

(for new applications under 37 C.F.R. § 1.53(b))

A

Case No.: C6556(V)
 Applicant: Michael COUGHLIN, David COLE and Charles Allen CRAWFORD
 For: CLEANING-IN-PLACE COMPOSITION AND METHOD FOR USING THE SAME
 Express Mail Label No.: EE 232 844 763 US
 Date Deposited: November 23, 1999
 UNUS No.: 99-0096-DIV

jc503 U.S. PTO
 09/447644
 11/23/99

To: Assistant Commissioner for Patents
 Box: Patent Application
 Washington, D.C. 20231

APPLICATION ELEMENTS

1. ☒ Fee Calculation (Box 13) and Authorization (Triplicate copies of this form are enclosed)
2. ☒ Specification and Claims (19) Total Pages
3. ☐ Formal or Informal Drawings () Total Sheets
4. ☒ Unexecuted Declaration
5. ☐ Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - a. ☐ Computer Readable Copy
 - b. ☐ Paper copy (identical to computer copy)
 - c. ☐ Statement verifying identify of above copies.


ACCOMPANYING APPLICATION PARTS

6. ☐ Information Disclosure Statement (IDS)/PTO-1449
7. ☐ Copies of IDS citations
8. ☐ Preliminary Amendment
9. ☒ Two (2) Return Receipt Postcards
10. ☐ Certified Copy of Priority Document
11. ☐ The benefit under 35 U.S.C. § 119 is claimed of the filing of:
12. ☐ Other:
13. ☒ The FILING FEE (including any claims introduced or cancelled by Preliminary Amendment) is calculated below:

CLAIMS					
FOR	NUMBER FILED		NUMBER EXTRA	RATE	BASIC FEE \$760.00
Total Claims	22 - 20		2	X \$ 18.00	36.00
Independent Claims	2 - 3			X \$ 78.00	
Multiple Claims	<u>Yes</u>	<u>No</u>		X \$260.00	
TOTAL FILING FEE . . .					\$796.00

14. [X] Charge \$796.00 to Deposit Acct. #12-1155. Triplicate copies of this letter are enclosed.
15. [X] The Commissioner is hereby authorized to charge any additional fees, which may be required, including all required fees under
- [X] 37 C.F.R. § 1.16;
 - [X] 37 C.F.R. § 1.17;
 - [X] 37 C.F.R. § 1.18.
16. [X] **Correspondence Address:**
Unilever Patent Department
45 River Road
Edgewater, New Jersey 07020

Respectfully submitted,



Edward A. Squillante, Jr.
Attorney of Record
Reg. #38,319

EAS/pod
(201) 840-2925

5 **CLEANING-IN-PLACE COMPOSITION**
 AND METHOD FOR USING THE SAME

10 **Field of the Invention**

 This invention is directed to a composition employable in a cleaning-in-place (CIP) system. More particularly, the invention is directed to a CIP composition that cleans, disinfects or both without requiring the use of a detergent. Also, described herein is a method for using such a CIP composition.

15 **Background of the Invention**

 It is extremely important to clean food processing facilities like breweries, dairy plants and carbonated beverage plants. Typically, such food processing facilities are cleaned by subjecting the internal or external portions of the machines that make up the facilities to a solution that reacts with the various soils present within the machines.

25 A conventional CIP system, for example, has several storage containers. Each storage container, independently, houses a solution (e.g., pre-rinse solution, cleaning solution, post-rinse solution) that is fed (non-simultaneously) into the facility targeted for cleaning or decontamination. Often, the solutions are pumped into the gas and liquid passages of the machines in the facilities being cleaned and then circulated
30 through the system until they are finally discharged to waste.

5 Typical CIP systems are known to employ chlorine. However, chlorine is not environmentally friendly and can form by-products with many organic substances found in the facilities being cleaned. These by-products are not desired and can be carcinogenic materials. Also, chlorine may result in carcinogenic by-products in, for example, the waste sites it is finally discharged to. Other CIP systems are known to
10 use active agents like hydrogen peroxide and peracetic acid. Such systems, however, require high levels of the active agents making their uses non-feasible, for example, from an economic standpoint. Furthermore, agents like peracetic acid tend to have a very pungent aroma.

15 It is of increasing interest to prepare a CIP composition that is environmentally friendly and economical to use. This invention, therefore, is directed to a CIP composition that does not result in the generation of environmentally unfriendly by-products and that unexpectedly does not require the use of a detergent to demonstrate superior cleaning properties. This invention is also directed to a method
20 for using the CIP composition in a food processing facility.

Background References

25 Efforts have been disclosed for cleaning processing equipment. In U.S. Patent No. 5,888,311, a process for cleaning equipment in the absence of a pre-rinse step is described.

5 Other efforts have been disclosed for cleaning equipment. In U.S. Patent No. 5,533,552, a CIP process comprising the step of circulating a cleaning liquid throughout equipment targeted for cleaning is described.

10 Still other efforts have been described for cleaning equipment. In U.S. Patent No. 5,064,561, a two part CIP system is described and the system utilizes an alkaline material and an enzyme.

Summary Of The Invention

15 In a first embodiment, this invention is directed to a CIP composition comprising a halogen dioxide, wherein the halogen dioxide is derived from a precursor alkali metal halite or alkaline earth metal halite, or both.

20 In a second embodiment, this invention is directed to a method for cleaning or disinfecting processing equipment with the CIP composition described in the first embodiment of this invention.

25 In a third embodiment, this invention is directed to a method for cleaning and disinfecting processing equipment with the CIP composition described in the first embodiment of this invention.

30 In a fourth embodiment, this invention is directed to processing equipment comprising, internally, the CIP composition of this invention or processing equipment coated with the CIP composition of this invention, or both.

5 **Detailed Description Of The Preferred Embodiments**

Regarding the halogen dioxide used in the CIP composition of this invention, such a compound preferably comprises fluorine, and most preferably, comprises chlorine, with chlorine dioxide being especially preferred. The halogen dioxide is
10 typically prepared by subjecting an alkali metal halite to an acid, like sulfuric acid.

Preferably however, the halogen dioxide is prepared by mixing a precursor with water and supplying current. The precursor added to the water is preferably an alkali metal halite, an alkaline earth metal halite, or both. The amount of precursor added to
15 the water is generally from about 1.0% to about 30.0%, and preferably, from about 2.0% to about 20.0%, and most preferably, from about 3.0% to about 7.0% by weight precursor, based on total weight of precursor and water, including all ranges subsumed therein.

The water that is mixed with the precursor may be tap water and is preferably soft water. The soft water preferably comprises substantially no calcium, magnesium and iron, and does comprise from about 10 ppm to about 5000 ppm, and preferably, from about 15 ppm to about 1000 ppm, and most preferably, from about 50 ppm to about 500 ppm sodium, based on total parts of the sodium and soft water, including
20 all ranges subsumed therein.

The CIP composition of this invention is typically produced by any conventional techniques capable of generating a halogen dioxide. Preferably, however, the CIP composition is produced in a commercially available halogen dioxide generator such as
30 those sold under the name of OXYCHLORe- by International Dioxide. This method is desired because it allows for the generation of halogen dioxide without requiring the

Case C6556(V)

- 5 addition of an acid. When preparing the composition, the precursor (e.g., Sodium Chlorite) and soft water solution reacts with electricity yielding the following reaction (composition):



10

The resulting composition is an illustrative example of the CIP composition which may be used in this invention. The preferred precursor solution is anthium dioxide and made commercially available from International Dioxide.

15

The amount of current supplied is limited only to the extent that halogen dioxide may be produced. Often, however, a 110 volt alternating current system is used whereby the system tends to deliver from about 10 to 20 amps of current.

20

When preparing the CIP composition of this invention, temperature and pressure may be maintained at any level that results in halogen dioxide generation. Preferably, however, the temperature is ambient and the pressure is atmospheric.

25

It is noted herein that the CIP composition of this invention unexpectedly displays both detergent and disinfectant properties when maintained in the pH range from about 6.0 to about 8.0. When superior cleaning properties are desired, the composition is maintained at a pH from about 7.0 to about 14.0, and preferably, from about 7.2 to about 13.0, and most preferably, from about 8.0 to about 10.0, including all ranges subsumed therein. When superior disinfectant properties are desired, the composition is maintained at a pH from about 1.0 to about 6.9, and preferably, from about 2.0 to about 6.0, and most preferably, from about 4.5 to about 5.5, including all ranges subsumed therein. Surprisingly, superior cleaning properties are obtained in

30

Case C6556(V)

- 5 the absence of a detergent. Superior cleaning and superior disinfectant properties are defined by the data present in the tables below.

The pH of the CIP composition of this invention may be modified by optionally adding acids, bases and/or employing buffers. Such acids include sulfuric and
10 phosphoric acid. The bases include sodium, potassium and lithium hydroxide and the buffers include bicarbonate, carbonate and bicarbonate/carbonate buffers and borax. The amount of pH modifiers that may be used is limited only to the extent that the desired pH is obtained. As to the buffers, the amount added is enough to keep the CIP composition of this invention substantially stable. Regarding the bases, such
15 bases may be generated directly within the process for synthesizing the halogen dioxide. This is often the case when the Oxychlor e-generator is used wherein the base (e.g., NaOH) may remain in the CIP composition or be drawn off.

After the CIP composition of this invention is prepared, the pH of the CIP
20 composition may be modified or buffered in the tank generator it is prepared in. Optionally, a separate tank may be used to modify or buffer the composition.

Subsequent to pH modifying and/or buffering, the CIP composition is pumped, via a pump and feed line, to the processing equipment targeted for cleaning,
25 disinfecting or both. To extent possible, the CIP composition is pumped through all internal portions of the equipment until it is finally discharged for recycling or waste. Moreover, the CIP composition of this invention may be pumped or sprayed on to the external surface of the equipment targeted for cleaning or disinfecting. The pumping is achieved via any art recognized pump. Such pumps may generally be classified as
30 peristaltic, diaphragm or positive displacement pumps. The pumps are typically manufactured by suppliers like Watson-Marlow, Inc. and Tri-Clover, Inc.. The

5 spraying devices which may be used, for example, to spray the external portion of the processing equipment are typically distributed through establishments like System Cleaners A/S. The pumps and spraying devices which may be used in this invention may also be purchased from sanitary and hygiene specialists like DiverseyLever. Moreover, it is within the scope of this invention to make and store the CIP
10 composition of this invention and use the composition as needed. It is also within the scope of this invention to make the CIP solution and to then feed the CIP solution directly to the pump responsible for delivering the composition. Still further, a combination of stored and newly made CIP composition may be fed to the pump responsible for delivering the composition.

15

As to the conduit that may be employed in this invention, such conduit is limited only to the extent that it is capable of transporting the CIP composition of this invention. The conduit is often a polymeric conduit or metal conduit, with stainless steel being especially preferred. Also, such conduit has an inside diameter ranging
20 from about 0.25 cm to about 20 cm, but preferably, is from about 2.5 cm to about 10 cm.

The rate at which the CIP composition is delivered to the processing equipment is limited only to the extent that the rate does not prevent the CIP composition from
25 cleaning and/or disinfecting the processing equipment targeted. Typically, however, the rate at which the CIP composition is delivered to the processing equipment is one which is selected or derived from maintaining a minimum linear velocity from about 1.5 to about 2.5 meters/second.

30 When the CIP composition is supplied to the processing equipment, one composition may be supplied having a single pH. It is also within the scope of this

Case C6556(V)

5 invention, however, to supply a CIP composition of a first pH followed by a CIP composition having a second pH. The alternating of CIP compositions having different pH values is often preferred when conditions of maximum cleaning and maximum disinfecting are desired.

10 The supplying of the CIP composition of this invention to processing equipment targeted for cleaning and/or disinfecting may be done in a manner such that the composition is fed into a single feed line of the processing equipment. In a preferred embodiment, the composition is fed into a feed line of each component of the processing equipment. A superior method for feeding solutions through a multitude of
15 feeding lines in processing equipment may be found in Docket No. 99-0420-UNI (filed concurrently herewith), commonly assigned to DiverseyLever, the disclosure of which is incorporated herein by reference.

It should be noted herein that the CIP composition of this invention comprises
20 halogen dioxide and a hydroxide. It is, however, within the scope of this invention for the composition to consist essentially of halogen dioxide, hydroxide and water. It is further within the scope of this invention for the composition to consist of halogen dioxide, hydroxide and water. Moreover, when the CIP composition of this invention is pumped and/or sprayed, the CIP composition may be subjected to pressure and
25 heat. Pressure and heat (e.g., temperature of the CIP composition) may vary and are only limited to the extent that the CIP composition may be used to clean and/or disinfect the processing equipment of concern.

The examples which follow below are provided to further illustrate and facilitate
30 an understanding of the present invention. Therefore, the examples are not meant to

Case C6556(V)

- 5 be limiting and modifications which fall within the scope and spirit of the claims are intended to be within the scope and spirit of the present invention.

Example 1

- 10 A 1 liter flask was charged with about 10.42 mL of anthium dioxide (5% Sodium Chlorite) as made commercially available by International Dioxide. About 3.2 mL of 1N H₂SO₄ were subsequently added to produce a solution having a pH of about 2.2. Deionized water was then added to produce 1 liter of total solution. The resulting chlorine dioxide solution (about 60% completion, 300 ppm) was used in the
15 experiments which follow.

Examples 2-6

- 20 For each of the five (5) experiments below, two quartz UV cells having a path length of 5.0 cm were each charged with 5.95 mL of a 0.1 molar sodium phosphate solution (to establish a buffered pH of about 11). The first cell was further charged with 0.6 mL of neat (conventional) root beer, as made commercially available. The second cell was further charged with 0.6 mL deionized water. Both cells were then charged in a manner set forth in Table I below. Using the contents of the second cell
25 as the blank, the absorbance of the resulting root beer solution was determined over the range of 440 to 700 nm, using a Hewlett-Packard 8452 UV/vis spectrophotometer. The absorbance over this wavelength range was integrated, and the percent (%) reduction in color of root beer was based on a comparison to the integrated absorbance of the control to which no CIP composition has been added.

30

Case C6556(V)

5

Table I*

Example	CIP Composition	Ppm	Ppm as	% Reduction of Color
2 (Control)	None	--	--	0.0
3	2.0 mL of 300ppm solution from Example 1 +3.45 mL H ₂ O	50	Chlorine dioxide	56.09
4	145 µL sodium hypochlorite solution (3.5%) +5.31 mL H ₂ O	200	Total chlorine	36.49
5	26 µL hydrogen peroxide solution (30%) +5.42 mL H ₂ O	300	Active oxygen	4.94
6	49 µL of peroxyacetic acid solution (35%) +5.40 mL of H ₂ O	300	Active oxygen	25.76

* The data in Table I above depicts (as color reduction) the superior and unexpected cleaning properties obtained when using chlorine dioxide in a simulated cleaning-in-place experiment. Further, these unexpected cleaning properties were obtained in the absence of a detergent.

Examples 7-12

Examples 7-12 are provided to demonstrate the superior disinfecting properties of the CIP composition of this invention. The examples were carried out in a manner set forth in Table II which follows:

Case C6556(V)

5

Table II***

Example**	CIP Composition/ Concentration	Cultures					
		Lactobacillus brevis	Bacillus cerus	Candida Albicans	Zygosacc- haromyces baillii	Rhizopus stolonifer	Byssochlamys nivea
7	Aqueous chlorine dioxide/about 15 ppm	About 9.9999	About 9.9999	About 9.9999	About 9.9999	About 99.99	About 99.99
8	Mixed halogen/about 25 ppm	About 99.9999	About 99.9999	About 99.9999	About 99.9999	About 99.99	About 99.99
9	Peroxyacetic acid/about 125 ppm	About 99.9999	About 99.99	About 99.99	About 99.99	<99	About 99.9
10	Aqueous chlorine dioxide/about 15 ppm	About 99.9999	About 99.9999	About 99.9999	About 99.9999	About 99.9999	About 99.9999
11	Mixed halogen/about 25 ppm	About 99.9999	About 99.9999	About 99.9999	About 99.9999	About 99.999	About 99.999
12	Peroxyacetic acid/about 125 ppm	About 99.9999	About 99.9999	About 99.9999	About 99.9999	<99	About 99.99

** The data from Examples 7-9 show the percent bacteria killed after the CIP composition and bacteria were combined for 30 seconds and the data from Examples 10-12 show the percent bacteria killed after the CIP composition and bacteria were combined for 2 minutes.

*** Examples 7-12 were conducted in the following manner.

5 **Number of Microbes in the Inoculum**

American Type Culture Collection cultures were transferred daily and maintained on agar slants containing the appropriate growth medium¹. A loopful of the culture was transferred into 10 ml of Butterfield's phosphate buffer pH 7.2

10 (NutraMax Products, Inc.) and agitated to obtain a homogenous turbid suspension. The actual concentration of microbes in suspension was estimated by its serial dilution in Butterfield's phosphate buffer and subsequent transfer of 0.1 ml of the dilution series into a Petri plate containing the appropriate agar growth medium. The inoculated Petri plates were incubated for 48-72 hours (at about 37°C) and the

15 resulting colonies counted with a Quebec colony counter. The number of colonies on the Petri plates multiplied by the serial dilution factor is equal to the number of microbes in 0.1 ml of inoculum.

20 **Number of Survivors in the Presence of CIP Composition**

Suspension test: 1 ml of each microbial suspension was mixed with 9 ml of each CIP composition containing 50 ppm CaCO_3 at 10/9 of the recommended use concentration (RUC) so that final concentration was exact RUC. After contact times

25 described above, 1 ml of the mixture was put to 9 ml of neutralizer² from which 0.1 ml of sample was plated onto the appropriate agar and incubated at 28°C for 48-72 hours before counting. The number of colonies present on the Petri plates multiplied by the serial dilution factor is equal to the number of microbes in 0.1ml that survived in the sanitizer solution.

30

Case C6556(V)

5 Per Cent Microbes Killed by CIP Composition

The per cent microbes killed by CIP composition is calculated by using the following equation:

10 (1) $[\text{Number of microbes per ml killed by CIP composition} - 1 / \text{Number of microbes per ml killed by the sanitizer solution}] \times 100$

15 (2) $\text{Number of microbes per ml killed by CIP composition} = \text{Number of microbes in } 0.1 \text{ ml of inoculum} \times 10 - \text{Number of microbes in } 0.1 \text{ ml} \times 10 \text{ that survived in the CIP composition.}$

¹Growth Media

Lactobacillus brevis	Bacillus cerus	Candida albicans	Zygosaccharomyces bailii	Rhizopus stolonifer	Byssoschlamys nivea
Nutrient Agar	Nutrient Agar	YM Agar	YM Agar	Malt Extract Agar	Malt Extract Agar

² Neutralizer Composition:

25	Lecithin	6.0 g
	NIH thioglycollate	1.0 g
	Histidine	2.0 g
	Phosphate buffer 0.25N	20.0 ml
	Na thiosulfate	2.0 g
	Tween 80	30.0 ml
30	d.i. water	balance to 1 L

Case C6556(V)

5 Starting from left to right in Table II, the 6 suspensions had a concentration of
8.2, 8.5, 8.0, 8.5, 7.5 and 8.1 log bacteria/mL, respectively. One (1) mL of
suspension and 9.0 mL of CIP composition were combined, resulting in the above
data. The pH of the chlorine dioxide CIP composition was 5.8, the mixed halogen is
sold by DiverseyLever under the name of Divosan MH and the peroxyacetic acid was
10 an aqueous solution having about 65% water.

The data in Table II demonstrates that the CIP compositions with halogen
dioxides unexpectedly result in superior disinfecting properties when significantly less
active is used, even in a CIP process.

5 We claim:

1. A cleaning-in-place composition comprising, in stoichiometric amounts, a halogen dioxide wherein the halogen dioxide is derived from a precursor alkali metal halite or alkaline earth metal halite, or both.

10

2. A composition according to claim 1 wherein the composition does not comprise a detergent.

15

3. A composition according to claim 1 wherein the halogen dioxide is fluorine dioxide, chlorine dioxide or a mixture thereof.

4. A composition according to claim 1 further comprising a hydroxide wherein the hydroxide is sodium hydroxide.

20

5. A composition according to claim 1 wherein the composition has a pH from about 6.0 to about 8.0.

6. A composition according to claim 1 wherein the composition has a pH from about 7.0 to about 14.0.

25

7. A composition according to claim 1 wherein the composition has a pH from about 1.0 to about 6.9.

30

8. A composition according to claim 1 wherein the precursor is an alkali metal halite, the alkali metal halite being sodium chlorite.

Case C6556(V)

5 9. A method for cleaning and disinfecting processing equipment, the method comprising the steps of:

(a) delivering a cleaning-in-place composition to the processing equipment; and

10 (b) removing the composition from the processing equipment,

wherein the composition comprises:

a halogen dioxide, the halogen dioxide being derived from a precursor alkali metal halite or alkaline earth metal halite, or both.

15

10. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the processing equipment is selected from the group consisting of brewery processing equipment, dairy plant processing equipment and carbonated beverage plant processing equipment.

20

11. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the halogen dioxide is fluorine dioxide, chlorine dioxide or a mixture thereof.

12. A method for cleaning and disinfecting processing equipment according to claim 25 9 wherein the halogen dioxide is chlorine dioxide.

13. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the composition further comprises a hydroxide wherein the hydroxide is sodium hydroxide.

30

Case C6556(V)

5 14. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the composition does not comprise a detergent.

15. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the composition has a pH from about 6.0 to about 8.0, or from about 7.0 to
10 about 14.0, or from about 1.0 to about 6.9.

16. A method for cleaning and disinfecting processing equipment according to claim 9 further comprising the step of delivering a second cleaning-in-place composition, the second cleaning-in-place composition having a pH which is different from the pH of
15 the cleaning-in-place composition.

17. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the precursor is an alkali metal halite, the alkali metal halite being sodium chlorite.
20

18. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the composition is delivered by pumping or spraying the composition to the processing equipment.

25 19. A method for cleaning and disinfecting processing equipment according to claim 18 wherein the composition is pumped into an internal portion of the processing equipment.

30 20. A method for cleaning and disinfecting processing equipment according to claim 18 wherein the composition is sprayed on to an external portion of the processing equipment.

Case C6556(V)

5

21. A method for cleaning and disinfecting processing equipment according to claim 9 wherein the composition is:

- 10
- (a) generated directly before delivery to the processing equipment, or
 - (b) generated, then stored, then delivered to the processing equipment, or
 - (c) both.

22. Processing equipment comprising, internally, or externally, or both, the cleaning-in-place composition of claim 1.

5

ABSTRACT OF THE DISCLOSURE

10 A composition for a cleaning-in-place system is described. The composition has
a halogen dioxide and a optionally hydroxide and does not require the use of a
detergent to display excellent cleaning and disinfecting properties on processing
equipment such as the equipment found in breweries, dairy plants and carbonated
beverage plants.

15

20

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (Includes Reference to PCT International Applications)	Case No. C6556(V)
--	----------------------

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

CLEANING-IN-PLACE COMPOSITION AND METHOD FOR USING THE SAME

the specification of which (check only one item below):

☒ is attached hereto.

☐ was filed as United States application Serial No. 09/ _____ on _____ and was amended on _____ (if applicable)

☐ was filed as PCT international application _____ on _____ and was amended under PCT Article 19 on _____ (if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, §119 of any foreign application(s) for patent or inventor's certificate or of any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

PRIOR FOREIGN/PCT APPLICATION(S) AND ANY PRIORITY CLAIMS UNDER 35 U.S.C. 119:

COUNTRY (if PCT, indicate "PCT")	APPLICATION NUMBER	DATE OF FILING (day, month, year)	PRIORITY CLAIMED UNDER 35 U.S.C. 119

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s) or PCT international application(s) designating the United States of America that is/are listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in that/those prior application(s) in the manner provided by the first paragraph of Title 35, United States Code §112. I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations §1.56(a) which occurred between the filing date of the prior application(s) and the national or PCT international filing date of this application.

PRIOR U.S. APPLICATIONS OR PCT INTERNATIONAL APPLICATIONS DESIGNATING THE U.S. FOR BENEFIT UNDER 35 U.S.C. 120.

U.S. APPLICATIONS		STATUS (CHECK ONE)		
U.S. APPLICATION NUMBER	U.S. FILING DATE	PATENTED	PENDING	ABANDONED

PCT APPLICATIONS DESIGNATING THE U.S.				
PCT APPLICATION NO.	PCT FILING DATE	U.S. SERIAL NUMBERS ASSIGNED (if any)		

COMBINED DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY (Includes Reference to PCT International Applications)	Case No. C6556(V)
--	----------------------

POWER OF ATTORNEY: As a named inventor, I hereby appoint the following attorney(s) and/or agents(s) to prosecute this application and transact all business in the Patent and Trademark Office connected therewith. (List name and registration number)

James J. Farrell, Esq., Reg. 26,162
Gerard J. McGowan, Jr., Esq., Reg. 29,412
Matthew Boxer, Esq., Reg. 28,495

Milton L. Honig, Esq., Reg. 28,617
Ronald A. Koatz, Esq., Reg. 31,774
Edward A. Squillante, Jr., Reg. 38,319

Neil Y. Gilbert, Esq., Reg. 35,156
Rimma Mitelman, Esq. Reg. 34,396
Alan A. Bornstein, Esq., Reg. 40,919

Send correspondence to:
Unilever Patent Department
45 River Road
Edgewater, New Jersey 07020

Direct Telephone Calls to: (name and telephone #):
Edward A. Squillante, Jr.
(201) 840-2925

201			
FULL NAME OF INVENTOR	FAMILY NAME COUGHLIN	FIRST GIVEN NAME MICHAEL	SECOND GIVEN NAME
RESIDENCE AND CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY

202			
FULL NAME OF INVENTOR	FAMILY NAME COLE	FIRST GIVEN NAME DAVID	SECOND GIVEN NAME
RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY

203			
FULL NAME OF INVENTOR	FAMILY NAME CRAWFORD	FIRST GIVEN NAME CHARLES	SECOND GIVEN NAME ALLEN
RESIDENCE & CITIZENSHIP	CITY	STATE OR FOREIGN COUNTRY	COUNTRY OF CITIZENSHIP
POST OFFICE ADDRESS	POST OFFICE ADDRESS	CITY	STATE & ZIP CODE/COUNTRY

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issuing thereon.

SIGNATURE OF INVENTOR	201	SIGNATURE OF INVENTOR	202	SIGNATURE OF INVENTOR	203
DATE		DATE		DATE	